

VINYL MATT WB20

FEATURES AND BENEFITS

- Anti-Viral ISO21702:2019
- Anti-Bacterial ISO22196:2011
- Durable and wipeable
- Matt finish
- Excellent opacity

PRODUCT DESCRIPTION

Vinyl Matt WB20 is an attractive finish that is tough and practical. The ideal choice for interior walls and ceilings where a modern flat matt finish is required. With the additional hygiene benefit providing Anti-Viral and Anti-Bacterial efficacy.

TYPICAL PHYSICAL FEATURES

PROPERTY	STERICOAT™ VINYL MATT WB20
Flashpoint	Not Applicable
Colour	Over 7000 colours plus Brilliant White and Magnolia
Dry film appearance	Matt Finish
Application	Brush and roller
Spread rate	15-16m ² per litre depending on surface texture and porosity
Wet film thickness	60 micrometres at 15-16m ² per litre
Dry film thickness	19 micrometres at 15-16m ² per litre
Dry - touch dry	2 hours @20°C Recoat possible after 4 hours
Pigment	Titanium Dioxide, coloured pigments and extenders
Binder	Vinyl acetate copolymer
Solvent	Water
Volume solids	32%
VOC Content	EU limit value for this product (cat.A/a): 30 g/l (2010) This product contains max. 2 g/l VOC
Anti-Viral ISO21702:2019	98.34% 1.78 R [R=(Ut-Uo)-(At-Uo)] Coronavirus (Feline Munich Strain)
Anti-Bacterial ISO022196:2011	99.99% >4 R [R=(Ut-Uo)-(At-Uo)] E. Coli 99.99% >4 [R=(Ut-Uo)-(At-Uo)] MRSA

PREPARATION

New surfaces

All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed with Universal Primer. Porous surfaces should be 'mist' coated with SteriCoat™ Vinyl Matt thinned with up to 40% clean water.

Previously decorated surfaces

All surfaces must be suitably dry, and free from anything that will interfere with the adhesion of the materials to be applied e.g., dirt, grease etc. Remove all loose, and failing or suspect paint. Remove grey and denatured surfaces by rubbing down with abrasive paper. Feather edges of sound paint. Remove all dust. Fill any fixing holes, cracks and shallow surface defects with Ready Mixed Filler. Patch prime bare and filled areas with Stain Blocking Primer. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning any areas are still contaminated with substances likely to cause staining and/or bleeding, patch prime with one coat of Stain Blocking

COATING SYSTEM

Apply two coats.

APPLICATION

Stir well before use. Apply by brush or roller. For airless spray (dilution may be required). For further information contact the Customer Relations Team.

CLEANING

Return surplus material to container. Wash with clean water immediately after use.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact our Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other SteriCoat™ Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost-free conditions this product will remain usable for up to two years if stored correctly and unopened.

**For all other support
please get in contact
with us:**

www.stericoat.co.uk
+44(0) 333 3355499



The information provided is given in good faith on the basis of practical experience and extensive laboratory tests. Many factors beyond Chem X's control and uniquely within the user's knowledge and control can affect the use and performance of a Chem X product in particular application. User is solely responsible for evaluating the Chem X product and determining whether it is fit for a particular purpose and suitable for user's method of application. Chem X makes no other warranties or conditions, express or implied, including, but not limited to, any implied warranty or condition of merchantability or fitness for a particular purpose or any implied warranty of non-infringement or any implied warranty or condition arising out of a course of dealing, custom or usage of trade. IF the Chem X product does not conform to this warranty, then the sole and exclusive remedy is, at Chem X's option, replacement of the Chem X product or refund of the purchase price. Please recycle. Printed in the United Kingdom