

# MID SHEEN MS40

## FEATURES AND BENEFITS

- Anti-Viral ISO21702:2019
- Anti-Bacterial ISO22196:2011
- Durable and wipeable
- Mid Sheen
- Excellent opacity

## PRODUCT DESCRIPTION

High-performance coating with an attractive, easy to apply, washable Mid Sheen. An alternative finish to Vinyl Matt and Vinyl Silk for interior walls and ceilings with the additional hygienic nano technology benefits, providing Anti-Viral and Anti-Bacterial efficacy.

## TYPICAL PHYSICAL FEATURES

PROPERTY	STERICOAT MS40
Flash point	Not applicable
Colour	Over 7000 colours plus Brilliant White and Magnolia
Dry film appearance	Mid Sheen
Application	Brush and roller
Spread rate	Up to 14m <sup>2</sup> per litre depending on surface texture and porosity.
Wet film thickness	71 micrometres at 14m <sup>2</sup> per litre
Dry film thickness	24 micrometres at 14m <sup>2</sup> per litre
Dry - touch dry	1-2 hours @20°C Recoat possible after 4 hours
Pigment	Titanium Dioxide, coloured pigments and extenders
Binder	Vinyl acetate copolymer
Solvent	Water
Volume solids	34%
VOC Content	EU limit value for this product (cat.A/a): 30 g/l (2010) This product contains max. 2 g/l VOC.
Anti-Viral ISO21702:2019	98.34% 1.78 R [R=(Ut-Uo)-(At-Uo)] Coronavirus (Feline Munich Strain)
Anti-Bacterial ISO22196:2011	99.99% >4 R [R=(Ut-Uo)-(At-Uo)] E. Coli 99.99% >4 [R=(Ut-Uo)-(At-Uo)] MRSA

## PREPARATION

### New surfaces

All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed with Universal Primer. Porous surfaces should be 'mist' coated with Mid Sheen thinned with up to 20% clean water.

### Previously decorated surfaces

All surfaces must be suitably dry, and free from anything that will interfere with the adhesion of the materials to be applied e.g., dirt, grease etc. Remove all loose, and failing or suspect paint. Feather edges of sound paint. Remove all dust. Fill any fixing holes, cracks and shallow surface defects with Ready Mixed Filler. Patch prime bare and filled areas with Stain Block Primer. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning any areas are still contaminated with substances likely to cause staining and/or bleeding, patch prime with one coat of Stain Block Primer. Bring forward patch primed areas with one coat of Mid Sheen.

## COATING SYSTEM

Apply two coats.

## APPLICATION

Stir well before use. Apply by brush or roller. For airless spray dilution may be required. For further information contact the Customer Relations Team.

## CLEANING

Return surplus material to container. Wash with clean water immediately after use.

## HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre-1960's painted surfaces as they may contain harmful lead. For further information contact our Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other SteriCoat™ Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

**For all other support  
please get in contact  
with us:**

[www.stericoat.co.uk](http://www.stericoat.co.uk)

+44(0) 333 3355499



The information provided is given in good faith on the basis of practical experience and extensive laboratory tests. Many factors beyond Chem X's control and uniquely within the user's knowledge and control can affect the use and performance of a Chem X product in particular application. User is solely responsible for evaluating the Chem X product and determining whether it is fit for a particular purpose and suitable for user's method of application. Chem X makes no other warranties or conditions, express or implied, including, but not limited to, any implied warranty or condition of merchantability or fitness for a particular purpose or any implied warranty of non-infringement or any implied warranty or condition arising out of a course of dealing, custom or usage of trade. IF the Chem X product does not conform to this warranty, then the sole and exclusive remedy is, at Chem X's option, replacement of the Chem X product or refund of the purchase price. Please recycle. Printed in the United Kingdom